



材料：铝6082或者A380 T6

表面处理：成品后硬质氧化，氧化薄膜厚度55-65微米，HV300-350

Note:

1. Hard oxidation: Oxidation film thickness 55 To 65um, HV300~350
2. All dimensions are finished dimension after hard oxidation.

ISSUE	MODIFICATIONS	APPD	DATE
1	Released for production		19thMay2014
2	Change the hard oxidation film thickness to 55~65um, add the hardness specification		27thOct2014

DRAWN BY	DATE	SCALE	HOLE TOL	GEN TOL
	19/May/2014		+/-0.05	0 +/-0,4
APP'D BY	DATE	DIM IN	ANGLES	0,0 +/-0,2
		mm	+/-0.5°	0,00+/-0,1

THIS DRAWING IS SUPPLIED IN CONFIDENCE AND THE COPYRIGHT THEREOF IS THE PROPERTY OF GOBOOF : IT MUST NOT BE USED BY A THIRD PARTY WITHOUT PRIOR PERMISSION. ©2008	
PROJECT	MURCIA
TITLE	OVEN
NO.OFF:	

DO NOT SCALE
IF IN DOUBT ASK



MATERIAL	AI 6082 T6	R.o.H.S. All material must comply with the requirements of European Directive 2002/95/EC on the restriction of the use of certain hazardous substances.
FINISH	Hard Oxidation	

DRG NO	A-0030	A4
		Sht 1 of 1